

TEST REPORT n. 1880-CPR-004-005-17

Initial Type Testing

Residential space heating appliances fired by wood pellets
EN 14785:2006

Manufacturer: KLOVER SRL
Via A. Volta, 8
37047 SAN BONIFACIO (VR)
Italy

Type designation: PFP 160 Glass

Type of appliance: Residential space heating appliances fired by wood pellets with water heat exchanger with direct and indirect water system.

Receipt date: February 10, 2017

Start test date: February 14, 2017

End test date: February 20, 2017

Testing laboratory: ACTECO SRL – Notified Body 1880
via Amman, 41
33084 Cordenons (PN)
Italy

Issue date: March 11, 2020

Head of Test Laboratory
Dr.ssa Claudia Marcuzzi

The results of the tests relate only to the tested appliance.
This test report shall not be reproduced except in full, without written approval of the laboratory.
The appliance was returned to the manufacturer after the end of tests.
All data is stored for 10 years

Pag. 1 / 3

TEST REPORT n. 1880-CPR-004-005-17

Task

ACTECO SRL was instructed to execute initial type testing to establish compliance according to the:

- European standard UNI EN 14785:2006 Residential space heating appliances fired by wood pellets
- UNI CEN/TS 15883:2009 Residential solid fuel burning appliances. Emission test methods
- Client's documents

The practical tests were performed in the laboratory in Cordenons (PN), via Amman, 41.

The type designation indicated in page 1 is identical to the already tested appliance designated "PFP18" The practical tests were performed in the laboratory in Cordenons (PN), via Amman, 41 (see Test Reports: n°1880-CPR- 004-17; n°1880-CPR- 004-CL-17; n°1880-CPR- 004-001-17).

In the type designations:

PFP 160 Glass

the difference regards the cover design. The main parts, components, combustion room, heating parts are identical.

Description of the appliance

Roomheater fired by wood with water heat exchanger.

The combustion air is taken from the test room.

Residential space heating appliances fired by wood pellets with direct and indirect water system.

The combustion air is taken from the test room.

Key data of appliance

Appliance	PFP 160 Glass	
Fuel		Wood pellet
Fuel throughput	kg/h	3,41
Total heating output	kW	15,8
Space heating output	kW	3,5
Water heating output	kW	12,3
CO emission based on 13% O ₂	mg/m ³	127
Efficiency	%	93,6
Flue gas temperature	°C	135,4
Necessary flue draught	Pa	9,9
Flue gas mass flow	g/s	7,8
Permissible maximum operating pressure	bar	2,5
Minimum clearance distances from exposed / combustibile materials	from rear wall	150 mm
	from side walls	150 mm

The results of the tests relate only to the tested appliance.
This test report shall not be reproduced except in full, without written approval of the laboratory.
The appliance was returned to the manufacturer after the end of tests.

All data is stored for 10 years

Pag. 2 / 3

TEST REPORT n. 1880-CPR-004-005-17

STATEMENTS OF THE TEST RESULTS

The following requirements of EN 14785:2006 are met:

- materials, design and construction requirements specified in clause 4 (as declared by the manufacturer);
- the safety requirements specified in clause 5;
- the performance requirements specified in clause 6;
- the installation and operating instructions requirements specified in clause 7;
- the marking information requirements specified in clause 8.

PERFORMANCE AT THE NOMINAL HEAT OUTPUT TEST			
Parameter		result	EN 14785:2006 limit
carbon monoxide [at 13% O ₂]	%	0,010	< 0,04
efficiency	%	93,6	> 75
PERFORMANCE AT THE REDUCED HEAT OUTPUT TEST			
Parameter		result	EN 14785:2006 limit
carbon monoxide [at 13% O ₂]	%	0,052	< 0,06
efficiency	%	96,0	> 70

The appliance **PPF 160 Glass of Klover srl** complies with the requirements of the harmonized European standard UNI EN 14785:2006.

Compliance with the clauses of the harmonized European standard UNI EN 14785:2006 confers a presumption of fitness of the appliance covered by annex ZA for the intended uses indicated by the quoted above normative; reference shall be made to the information accompanying the CE marking.

The results of the tests relate only to the tested appliance.
This test report shall not be reproduced except in full, without written approval of the laboratory.
The appliance was returned to the manufacturer after the end of tests.
All data is stored for 10 years

Pag. 3 / 3