





TEST REPORT n. 1880-CPR-009-011-19

Initial Type Testing

Roomheaters fired by solid fuels EN 13240:2001 EN 13240:2001/AC:2006 EN 13240:2001/A2:2004/AC:2007 EN 13240:2001/A2:2004/AC:2006 EN 13240:2001/A2:2004

Manufacturer: KLOVER SRL

Via A. Volta, 8

37047 SAN BONIFACIO (VR)

Italy

Type designation: ALTEA COUNTRY

Type of appliance: Roomheater fired by wood with water heat exchanger.

Receipt date: January 22, 2019

Start test date: January 29, 2019

End test date: February 04, 2019

Testing laboratory: ACTECO SRL – Notified Body 1880

via Amman, 41

33084 Cordenons (PN)

Italy

Issue date: October 08, 2020

Head of Test Laboratory
Dr.ssa Claudia Marcuzzi







TEST REPORT n. 1880-CPR-009-011-19

Task

ACTECO SRL was instructed to execute initial type testing to establish compliance according to the:

- UNI EN 13240:2006 (EN 13240:2001 + EN 13240:2001/A2:2004 + EN 13240:2001/A2:2004/AC:2006 + EN 13240:2001/A2:2004/AC:2007 + EN 13240:2001/AC:2006). Roomheaters fired by solid fuels.
- UNI CEN/TS 15883:2009 Residential solid fuel burning appliances. Emission test methods
- Client's documents

The practical tests were performed in the laboratory in Cordenons (PN), via Amman, 41.

The type designations indicated in page 1 is identical to the already tested appliance designated "**ALTEA 110**". The practical tests were performed in the laboratory in Cordenons (PN), via Amman, 41 (see Test Reports: n°1880-CPR- 009-19; n°1880-CPR- 009-CL-19; n°1880-CPR- 009-001-19).

In the type designation:

ALTEA COUNTRY

the difference regards the cover design. The main parts, components, combustion room, heating parts are identical.

Description of the appliance

Roomheater fired by wood with water heat exchanger.

The combustion air is taken from the test room.

Key data of appliance

Appliance	ALTEA COUNTRY		
Fuel	wood logs		
Fuel throughput	kg/h	3,8	
Total heating output	kW	14,7	
Space heating output	kW	6,9	
Water heating output	kW	7,8	
CO emission based on 13% O ₂	mg/m³	816	
Efficiency	%	89,4	
Flue gas temperature	°C	131	
Necessary flue draught	Pa	9,4	
Flue gas mass flow	g/s	11,7	
Permissible maximum operating pressure	bar	2,5	
Minimum clearance distances from exposed / combustible materials	from rear wall from side walls		10 mm iso 0 mm

The results of the tests relate only to the tested appliance.

This test report shall not be reproduced except in full, without written approval of the laboratory.

The appliance was returned to the manufacturer after the end of tests.

All data is stored for 10 years







TEST REPORT n. 1880-CPR-009-011-19

STATEMENTS OF THE TEST RESULTS

The following requirements of UNI EN 13240:2006 (EN 13240:2001 + EN 13240:2001/A2:2004 + EN 13240:2001/A2:2004/AC:2006 + EN 13240:2001/A2:2004/AC:2007 + EN 13240:2001/AC:2006 are met:

- materials, design and construction requirements specified in clause 4 (as declared by the manufacturer);
- the safety requirements specified in clause 5;
- the performance requirements specified in clause 6;
- the installation and operating instructions requirements specified in clause 7;
- the marking information requirements specified in clause 8.

PERFORMANCE AT THE NOMINAL HEAT OUTPUT TEST				
Parameter		result	EN 13240 limit	
carbon monoxide [at 13% O ₂]	%	0,065	< 1	
efficiency	%	89,4	> 50	

The appliance **ALTEA COUNTRY** of **KLOVER SRL** comply with the requirements of the harmonized European standard UNI EN 13240:2006 (EN 13240:2001 + EN 13240:2001/A2:2004 + EN 13240:2001/A2:2004/AC:2006 + EN 13240:2001/A2:2004/AC:2006).

Compliance with the clauses of the harmonized European standard UNI EN 13240:2006 confers a presumption of fitness of the appliance covered by annex ZA for the intended uses indicated by the quoted above normative; reference shall be made to the information accompanying the CE marking.